

DEPARTMENT OF TRANSPORTATION

STATE OF GEORGIA

SUPPLEMENTAL SPECIFICATION

Section 456—Indentation Rumble Strips

Delete Section 456 and substitute the following:

456.1 General Description

This work includes constructing rumble strips on paved shoulders or centerlines by milling or grinding 1/2 in (13 mm) deep depressions into the finished surface as shown in the Plans.

456.1.01 Definitions

Skip ground in place rumble strips—Rumble strips placed with 28 ft (8.5 m) of strips and 12 ft (3.7 m) of clear space between.

Continuous ground in place rumble strips—Rumble strips placed continuously.

Edge line rumble strips – Rumble strips placed continuously on the edge line traffic stripe.

Centerline rumble stripes – Rumble strips placed continuously on the centerline traffic striping.

456.1.02 Related References

A. Standard Specifications

General Provisions 101 through 150.

B. Referenced Documents

General Provisions 101 through 150.

456.1.03 Submittals

General Provisions 101 through 150.

456.2 Materials

General Provisions 101 through 150.

456.2.01 Delivery, Storage, and Handling

General Provisions 101 through 150.

456.3 Construction Requirements

456.3.01 Personnel

General Provisions 101 through 150.

456.3.02 Equipment

A. Cutting Tool

Use a cutting tool that meets these requirements:

- Has independent suspension from the power unit to allow the tool to self-align with the slope of the shoulder
- Is equipped with guides to provide consistent alignment of each line of indentations in relation to the roadway
- Houses a single rotary-type milling/grinding head in line in the direction of travel
- The cutting tips on the milling/grinding head are arranged to provide a smooth cut with no more than 0.05 in (1 mm) between the peaks and valleys

Section 456—Indentation Rumble Strips

456.3.03 Preparation

General Provisions 101 through 150.

456.3.04 Fabrication

General Provisions 101 through 150.

456.3.05 Construction

A. Indentations

Form the rumble strip indentations as follows:

1. For traveled ways opened to traffic, install the indentations within ten calendar days.
2. Ensure the finished indentations conform to the following:
 - a. Indentations have a concave circular shape and are spaced 12 in (300 mm) center to center.
 - b. Skip, continuous, and centerline rumble strips indentation dimensions:
 - 7 in (175 mm) wide with a 5 in (125 mm) gap in the direction of travel
16 in (400 mm) long when measured perpendicular to the direction of travel.
 - Minimum 1/2 in (13 mm) maximum 5/8 in (16 mm) deep at center.
 - c. Edge line rumble strip indentation dimension:
 - 7 in (175 mm) wide with a 5 in (125 mm) gap in the direction of travel
 - 6 in (150 mm) long when measured perpendicular to the direction of travel.
 - Minimum 1/2 in (13 mm) maximum 5/8 in (16 mm) deep at center.

Excess waste material resulting from the operation may be swept to the grassed shoulder and spread where applicable. If an adjacent grassed shoulder is not available, or if directed by the Engineer, remove and dispose of the waste material in a manner approved by the Engineer.

456.3.06 Quality Acceptance

General Provisions 101 through 150.

456.3.07 Contractor Warranty and Maintenance

General Provisions 101 through 150.

456.4 Measurement

Indentation rumble strips are measured by the gross linear mile (kilometer). The Plan quantity is the pay quantity unless the Engineer makes authorized changes. No deductions will be made for intersections, ramps, bridges, or skips.

456.4.01 Limits

General Provisions 101 through 150.

456.5 Payment

Payment will be made at the Contract Unit Price bid per gross linear mile (kilometer). Payment is full compensation for furnishing equipment and labor and for satisfactorily performing the work.

Payment will be made under:

Item No. 456	Indentation rumble strips—ground in place (continuous)	Per gross linear mile (kilometer)
Item No. 456	Indentation rumble strips—ground in place (skip)	Per gross linear mile (kilometer)
Item No. 456	Indentation edge linerumble strips—ground in place (continuous)	Per gross linear mile (kilometer)
Item No. 456	Indentation centerline rumble strips—ground in place (continuous)	Per gross linear mile (kilometer)

456.5.01 Adjustments

General Provisions 101 through 150.

Office of Traffic Operations