PARCEL 69 REQ'D R/W KC687

PNT	OFFSET/ DIST		STATION/ BEARING	ALIGNMENT
SVX056742	88.20	R	483+07.52	S.R. 133
	91.68		S 18°34'59" E	
KC50745	90.51	R	484+00.00	S.R. 133
	91.83		N 21°48'39" W	
KC50748	93.37	R	483+07.37	S.R. 133
	5.17		N 71°26'10" E	
SVX056742	88.20	R	483+07.52	S.R. 133

REQD R/W = 237.00 SF
REQD R/W = 0.005 ACRES
REMAINDER = +/- 0.98 ACRES

PARCEL 69 REQ'D DRWY. EASM'T. KC688

PNT	OFFSET		STATION	ALIGNMENT
SVX056739	92.13	R	485+07.25	S.R. 133
KC50786	126.00	R	485+06.91	S.R. 133
KC50787	126.00	R	484+58.00	S.R. 133
KC50788	91.53	R	484+58.00	S.R. 133
SVX056739	92.13	R	485+07.25	S.R. 133

PARCEL 70 REQ'D EASM'T. KC772

PNT	OFFSET/ DIST		STATION/ BEARING	ALIGNMENT
SVX056734	92.63	R	486+64.90	S.R. 133
	58.10		S 18°34'59" E	
KC51134	92.65	R	487+23.00	S.R. 133
	17.35		S 71°23'58" W	
KC51138	110.00	R	487+23.00	S.R. 133
	58.10		N 18°36'02" W	
KC51139	110.00	R	486+64.90	S.R. 133
	17.37		N 71°25'23" E	
SVX056734	92.63	R	486+64.90	S.R. 133

REQD EASMT = 1008.40 SF
REQD EASMT = 0.023 ACRES

PARCEL 70 REQ'D EASM'T. KC773

PNT	OFFSET/ DIST		STATION/ BEARING	ALIGNMENT
KC50791	92.68	R	488+30.00	S.R. 133
	50.69		S 18°34'59" E	
SVX056730	92.70	R	488+80.69	S.R. 133
	17.46		S 63°41'26" W	
KC51133	110.00	R	488+83.03	S.R. 133
	53.03		N 18°36'02" W	
KC50790	110.00	R	488+30.00	S.R. 133
	17.32		N 71°23'58" E	
KC50791	92.68	R	488+30.00	S.R. 133

REQD EASMT = 897.52 SF
REQD EASMT = 0.021 ACRES
TOTAL REQD EASMT = 1905.92 = 0.044 ACRES
TOTAL LOT SIZE = 2.0 ACRES

PARCEL 70 REQ'D DRWY. EASM'T. KC689

PNT	OFFSET		STATION	ALIGNMENT
KC51134	92.65	R	487+23.00	S.R. 133
KC51135	92.67	R	487+77.00	S.R. 133
KC51136	120.00	R	487+77.00	S.R. 133
KC51137	120.00	R	487+23.00	S.R. 133
KC51134	92.65	R	487+23.00	S.R. 133

PARCEL 71 REQ'D DRWY. EASM'T. KC690

PNT	OFFSET		STATION	ALIGNMENT
SVX056730	92.70	R	488+80.69	S.R. 133
KC50792	92.72	R	489+40.00	S.R. 133
KC50793	115.00	R	489+40.00	S.R. 133
KC50789	115.00	R	488+83.71	S.R. 133
SVX056730	92.70	R	488+80.69	S.R. 133

PARCEL 72 REQ'D R/W KC691

PNT	OFFSET/ DIST		STATION/ BEARING	ALIGNMENT
SVX056774	37.26	L	490+04.32	S.R. 133
	46.42		S 89°01'50" E	
KC50763	81.00	L	490+19.87	S.R. 133
	180.13		S 18°36'02" E	
KC50762	81.00	L	492+00.00	S.R. 133
	12.00		N 71°23'58" E	
KC50798	93.00	L	492+00.00	S.R. 133
	47.46		S 20°04'25" E	
KC50799	94.22	L	492+47.44	S.R. 133
	60.52		N 89°01'50" W	
SVX056847	37.19	L	492+27.17	S.R. 133
	222.85		N 18°34'59" W	
SVX056774	37.26	L	490+04.32	S.R. 133

REQD R/W = 10322.68 SF
REQD R/W = 0.237 ACRES
REMAINDER = +/- 0.83 ACRES

PARCEL 72 REQ'D EASM'T. KC759

PNT	OFFSET/ DIST		STATION/ BEARING	ALIGNMENT
KC50763	81.00	L	490+19.87	S.R. 133
	176.43		S 89°01'50" E	
SVX056777	247.24	L	490+78.96	S.R. 133
	86.04		S 18°34'59" E	
KC51075	247.21	L	491+65.00	S.R. 133
	107.21		S 71°23'58" W	
KC51076	140.00	L	491+65.00	S.R. 133
	25.50		S 60°05'22" W	
KC51077	115.00	L	491+70.00	S.R. 133
	34.00		S 71°23'58" W	
KC50796	81.00	L	491+70.00	S.R. 133
	150.13		N 18°36'02" W	
KC50763	81.00	L	490+19.87	S.R. 133

REQD EASMT = 19446.43 SF
REQD EASMT = 0.446 ACRES

PARCEL 72 REQ'D DRWY. EASM'T. KC692

PNT	OFFSET		STATION	ALIGNMENT
KC50796	81.00	L	491+70.00	S.R. 133
KC51077	115.00	L	491+70.00	S.R. 133
KC50797	115.00	L	491+85.00	S.R. 133
KC50798	93.00	L	492+00.00	S.R. 133
KC50762	81.00	L	492+00.00	S.R. 133
KC50796	81.00	L	491+70.00	S.R. 133

PARCEL 73 REQ'D DRWY. EASM'T. KC693

PNT	OFFSET		STATION	ALIGNMENT
KC50800	92.81	R	492+58.00	S.R. 133
KC50801	92.83	R	493+24.00	S.R. 133
KC50802	120.00	R	493+24.00	S.R. 133
KC50803	120.00	R	492+58.00	S.R. 133
KC50800	92.81	R	492+58.00	S.R. 133

PARCEL 74 REQ'D R/W KC694

PNT	OFFSET/ DIST		STATION/ BEARING	ALIGNMENT
SVX056847	37.19	L	492+27.17	S.R. 133
	60.52		S 89°01'50" E	
KC50799	94.22	L	492+47.44	S.R. 133
	302.66		S 20°04'25" E	
KC51142	102.00	L	495+50.00	S.R. 133
	190.67		S 14°59'32" E	
KC50794	90.00	L	497+40.29	S.R. 133

ARC LENGTH = 1032.460
CHORD BEAR = S 27°16'28" E
LNTH CHORD = 1028.521
RADIUS = 3410.000
DEGREE = 1° 40' 48''

KC51160	90.00	L	508+00.00	S.R. 133
	194.89		S 41°24'30" E	
KC51161	103.00	L	510+00.00	S.R. 133
	161.03		S 35°41'54" E	
KC50808	89.31	L	511+65.00	S.R. 133

ARC LENGTH = 1593.489
CHORD BEAR = N 30°40'36" W
LNTH CHORD = 1581.683
RADIUS = 3774.770
DEGREE = 1° 31' 4''

KC50828	37.10	L	495+43.94	S.R. 133
	316.77		N 18°34'59" W	
SVX056847	37.19	L	492+27.17	S.R. 133

REQD R/W = 60177.76 SF
REQD R/W = 1.381 ACRES
REMAINDER = +/- 124 ACRES

PARCEL 74 REQ'D EASM'T. KC695

PNT	OFFSET/ DIST		STATION/ BEARING	ALIGNMENT
KC50812	96.73	L	493+45.00	S.R. 133
	12.27		N 71°23'58" E	
KC50811	109.00	L	493+45.00	S.R. 133
	205.02		S 19°26'20" E	
KC51143	112.00	L	495+50.00	S.R. 133
	190.67		S 14°59'32" E	
KC50814	100.00	L	497+40.29	S.R. 133

ARC LENGTH = 543.718
CHORD BEAR = S 23°10'55" E
LNTH CHORD = 543.139
RADIUS = 3400.000
DEGREE = 1° 41' 6''

KC50815	100.00	L	503+00.00	S.R. 133
	10.00		S 62°14'13" W	
KC50816	90.00	L	503+00.00	S.R. 133

ARC LENGTH = 545.317
CHORD BEAR = N 23°10'55" W
LNTH CHORD = 544.737
RADIUS = 3410.000
DEGREE = 1° 40' 48''

KC50794	90.00	L	497+40.29	S.R. 133
	190.67		N 14°59'32" W	
KC51142	102.00	L	495+50.00	S.R. 133
	205.07		N 20°04'25" W	
KC50812	96.73	L	493+45.00	S.R. 133

REQD EASMT = 9630.90 SF
REQD EASMT = 0.221 ACRES

PARCEL 74 REQ'D EASM'T. KC696

PNT	OFFSET/ DIST		STATION/ BEARING	ALIGNMENT
KC50824	96.57	L	510+89.00	S.R. 133
	8.43		N 49°19'15" E	
KC50825	105.00	L	510+89.00	S.R. 133
	205.18		S 39°36'51" E	
KC50826	95.00	L	513+00.00	S.R. 133
	3.99		S 45°51'60" W	
KC50827	91.01	L	513+00.00	S.R. 133

ARC LENGTH = 131.532
CHORD BEAR = N 43°46'06" W
LNTH CHORD = 131.525
RADIUS = 3774.770
DEGREE = 1° 31' 4''

KC50808	89.31	L	511+65.00	S.R. 133
	74.34		N 35°41'54" W	
KC50824	96.57	L	510+89.00	S.R. 133

REQD EASMT = 2010.04 SF
REQD EASMT = 0.046 ACRES

PARCEL 74 REQ'D EASM'T. KC697

PNT	OFFSET/ DIST		STATION/ BEARING	ALIGNMENT
KC50829	93.12	L	516+50.00	S.R. 133
	11.88		N 40°08'13" E	
KC50830	105.00	L	516+50.00	S.R. 133
	245.85		S 51°30'14" E	
KC50831	105.00	L	519+00.00	S.R. 133
	11.97		S 37°53'06" W	
KC50832	93.03	L	519+00.00	S.R. 133
	103.20		N 52°06'42" W	
KC50833	93.03	L	517+96.80	S.R. 133

ARC LENGTH = 143.142
CHORD BEAR = N 51°01'32" W
LNTH CHORD = 143.134
RADIUS = 3774.770
DEGREE = 1° 31' 4''

KC50829	93.12	L	516+50.00	S.R. 133

REQD EASMT = 3138.67 SF
REQD EASMT = 0.072 ACRES

PARCEL 74 REQ'D EASM'T. KC698

PNT	OFFSET/ DIST		STATION/ BEARING	ALIGNMENT
KC51220	93.02	L	521+00.00	S.R. 133
	200.30		S 55°15'31" E	
KC50834	104.00	L	523+00.00	S.R. 133
	97.29		S 64°34'48" E	
KC50835	125.00	L	523+95.00	S.R. 133
	98.51		N 43°42'41" E	
KC50836	223.00	L	524+05.00	S.R. 133
	155.00		S 52°06'54" E	
KC50837	223.00	L	525+60.00	S.R. 133
	110.86		S 24°51'06" W	
KC50838	115.00	L	525+85.00	S.R. 133
	74.03		S 49°04'33" E	
KC50841	111.07	L	526+58.93	S.R. 133
	31.21		N 87°31'50" W	
SVX056848	92.99	L	526+33.49	S.R. 133
	533.49		N 52°06'42" W	
KC51220	93.02	L	521+00.00	S.R. 133

REQD EASMT = 27255.14 SF
REQD EASMT = 0.626 ACRES
TOTAL REQD EASMT = 42034.75 SF = 0.965 ACRES

PARCEL 74 REQ'D DRWY. EASM'T. KC699

PNT	OFFSET		STATION	ALIGNMENT
KC50809	95.70	L	493+05.00	S.R. 133
KC50810	109.00	L	493+05.00	S.R. 133
KC50811	109.00	L	493+45.00	S.R. 133
KC50812	96.73	L	493+45.00	S.R. 133
KC50809	95.70	L	493+05.00	S.R. 133

PROPERTY AND EXISTING R/W LINE
REQUIRED R/W LINE
CONSTRUCTION LIMITS
EASEMENT FOR CONSTR & MAINTENANCE OF SLOPES
EASEMENT FOR CONSTR OF SLOPES
EASEMENT FOR CONSTR OF DRIVES

BEGIN LIMIT OF ACCESS.....BLA
END LIMIT OF ACCESS.....ELA
LIMIT OF ACCESS
REQ'D R/W & LIMIT OF ACCESS

DATE	REVISIONS	DATE	REVISIONS
12/20/2011	REVISED R/W, EASM'T, AND DRWY EASM'T PARCEL 74		
02/01/2012	REVISED EASM'T AND REMOVED DRWY EASM'T TABLES PARCEL 74		
04/25/2012	REVISED EASEMENT PARCEL 74		

STATE OF GEORGIA
DEPARTMENT OF TRANSPORTATION

RIGHT OF WAY MAP

PROJECT NO: STP00-0000-00(545)
COUNTY: BROOKS
LAND LOT NO: 318,327
LAND DISTRICT: 12
GMD 660
DATE 05-06-11 SH 60 OF 64

1/5/2009