STATE	PROJECT NUMBER	SHEET NO.	TOTAL SHEETS
GA	CSBRG-0007-00(248)	68	84

VOID

SEDIMENT STORAGE

The site has a total disturbed area of 3.45 acres. The following table summarizes the required and available sediment storage for every outfall on this project. The Contractor shall provide and maintain the storage volumes for the BMP's specified in this table.

Location	Total Drainage Area (acres)	Disturbed Area (acres)	Required Sediment storage Volume (cu yd)	Total Storage volume provided (cu yd)	Sediment Basins		Check Dams		Inlet sediment Traps		Silt Fence	
					Pond *	Total Volume (Cu.Yd.)	Number of Devices	Total Volume (Cu.Yd.)	Number of Devices	Total Volume (Cu.Yd.)	Length of Silt Fence (Linear Feet)	Storage Volume (Cu.Yd.)
Total Sheet Flow	3.45	3.45	231.15	530.26	N/A	0	N/A	0	4	2.88	2127.6	527.38

In order to prevent runoff from bypassing inlet sediment traps, a temporary sump shall be installed around all inlet sediment traps that are not located in a low point or an excavated sump. Construct temporary sumps in accordance with Construction Detail D-24C. Temporary sumps shall be installed in a manner that ensures stormwater does not bypass the inlet. The Contractor may submit alternate temporary containment berm designs to the Project Engineer for approval.

The Disturbance Activities consist of Clearing and Grubbing, Removal of Existing Pavement Structure, Removal of Fill, Placement of Fill, and Grading. BMP's as shown on the ESPCP will be adequate to control sediment runoff at this location. Land disturbance activities associated with constructing and removing a sediment basin at this location would cause adverse impacts.

USE OF ALTERNATIVE AND/OR ADDITIONAL BMPS

No alternative or additional BMPs will be used on this project.

DISCHARGES INTO, OR WITHIN ONE LINEAR MILE UPSTREAM OF AND WITHIN THE SAME WATERSHED AS, ANY PORTION OF A BIOTA IMPAIRED STREAM SEGMENT

All outfalls are either located further than 1 linear mile upstream or outside of the watershed of an impaired Stream Segment that has been listed for criteria violated, "Bio F" (impaired Fish Community) and/or "Bio M" (impaired Macro Invertebrate Community), within Category 4a, 4b or 5, and the potential cause is either "NP" (nonpoint source) or "UR" (urban runoff).

STREAM BUFFER ENCROACHMENT

Stream Buffers are not impacted by this project.

MONITORING GENERAL NOTES:

The total site size is 4.40 acres. Representative sampling may be utilized on this project. The characteristics of the individual watersheds along the project corridor have been carefully evaluated and compared on the basis of drainage characteristics, watershed size, land disturbance and earth work. After evaluation of these items as presented in the projects drainage area maps, hydrology and hydraulic studies, construction plans and erosion sedimentation and pollution control plans, it has been determined that the increase in turbidity at the specified locations will be representative of the increase in turbidity for all waters leaving the site. Approved primary and alternate representative monitored feature are identified in the table below.

MONITORING FEATURE	PRIMARY OR ALTERNATE FEATURE	LOCATION (STATION AND OFFSET)	NAME OF RECEIVING WATER.	APPLICABLE CONSTRUCTION STAGE FOR MONITORING	SAMPLING TYPE (OUTFALL OR RECEIVING WATER)	DRAINAGE AREA FOR THE RECEIVING WATER (SQ. MI.)	DISTURBED AREA (ACRES)	WARM OR COLD WATER STREAM	APPENDIX B NTU VALUE (OUTFALL MONITORING ONLY)	ALLOWABLE NTU INCREASE (FOR RECEIVING WATER)	LOCATION DESCRIPTION
1 UP	PRIMARY	119+17. 70 FT L	FISHPOND DRAIN	ALL	RECEIVING WATER	84.40	0.00	WARM	N/A	25	UPSTREAM
1 DN	PRIMARY	117+94. 70 FT R	FISHPOND DRAIN	ALL	RECEIVING WATER	84.40	3.45	WARM	N/A	25	DOWNSTREAM

The primary monitored feature specified should be used as the initial sampling location. The alternate monitored feature may be used if additional sampling is required and/or if the primary monitored feature is no longer located within the active phase of construction.

MONITORING SAMPLING METHODS & PROCEDURES

See Special Provision 167 and other contract documents for Monitoring Sampling Methods and Procedures.

READY MIX CHUTE WASH-DOWN

The washing of ready-mix concrete drums and dump truck bodies used in the delivery of Portland cement concrete is prohibited on this site.

In accordance with Standard Specification 107: Legal Regulations and Responsibility to the Public, only the discharge chute utilized in the delivery of Portland cement concrete may be rinsed free of fresh concrete remains. The Contractor shall excavate a pit outside of State water buffers, at least 25 feet from any storm drain and outside of the travelled way, including shoulders, for a wash-down pit. The pit shall be large enough to store all wash-down water without overtopping. Immediately after the wash-down operations are completed and after the wash-down water has soaked into the ground, the pit shall be filled in, and the ground above it shall be graded to match the elevation of the surrounding areas. Alternate wash-down plans must be approved by the Project Engineer.

Wash-down plans describe procedures that prevent wash-down water from entering streams and rivers. Never dispose of wash-down water down a storm drain. Establish a wash-down pit that includes the following: (1) a location away from any storm drain, stream, or river, (2) access to the vehicle being used for wash down, (3) sufficient volume for wash-down water, and (4) permission to use the area for wash-down.

On sites where permission or access to excavate a wash-down pit is unavailable, the Contractor may have to wash-down into a sealable 55-gallon drum or other suitable container and then transport the container to a proper disposal site. For additional information, refer to the Georgia Small Business Environmental Assistance Program's "A Guide for Ready Mix Chute/Hopper Wash-down".

RETENTION OF RECORDS

The Department will retain records in accordance with Part IV.F of the General Permit GAR 10002.

GEORGIA
DEPARTMENT OF TRANSPORTATION

REVISION DATES

STATE OF GEORGIA
DEPARTMENT OF TRANSPORTATION

OFFICE: DISTRICT 4

ESPC GENERAL NOTES

CR 226 / BURKE RD
@ FISHPOND DRAIN

DRAWING No. 51-002

3/1/2007 GPLN 007248EGN1.dgn MPDB Obs 1"=24"63