	CODE	PRACTICE STD :SPC's :SECTION	DETAIL	DESCRIPTION
	Sd2-P	SEE THE MANUAL FOR EROSION AND SEDIMENT CONTROL IN GEORGIA SIXTH EDITION FOR ADDITIONAL INFORMATION.		ONCE PAVEMENT HAS BEEN INSTALLED, OR ON EXISTING INLETS, A CURB INLET FILTER SHALL BE INSTALLED ON INLETS RECEIVING RUNOFF FROM DISTURBED AREAS. THIS METHOD OF INLET PROTECTION SHALL BE REMOVED IF SAFETY HAZARD IS CREATED. PIG-IN-A-BLANKET: 8 IN CMU WRAPPED IN FILTER FABRIC OR GRAVEL BAGS CONSTRUCTED BY WRAPPIND *57 STONE WITH FILTER FABRIC, WIRE, PLASTIC MESH, OR EQUIVALENT MATERIAL. A GAP OF 4 INCHES SHALL BE LEFT BETWEEN THE INLET FILTER AND THE INLET.
		LINE CODE Sd2-P		
		LINE CODE		
		LINE CODE		
		LINE CODE		
		LINE CODE		

	CODE	PRACTICE STD :SPC's :SECTION	DETAIL	DESCRIPTION
		LINE CODE		
		LINE CODE		
		LINE CODE		
		LINE CODE		

NOTE:
1. DO NOT USE EROSION CONTROL ITEMS IN A FLOWING STREAM OR IN A TIDAL AREA BELOW HIGH TIDE.
2. FOR ADDITIONAL INFORMATION ON THE DESIGN AND APPLICATION OF EROSION CONTROL MEASURES SEE THE GEORGIA SOIL AND WATER CONSERVATION COMMISSION. "MANUAL FOR EROSION AND SEDIMENT CONTROL IN GEORGIA".

BY	DATE	DEPARTMENT OF TRANSPORTATION STATE OF GEORGIA	
	REVISION	EROSION CONTROL LEGEND AND UNIFORM CODE SHEET SHEET OF NO SCALE	
		NUMBER EC-L	DRAWING No. 52-07