

TEMPORARY SEDIMENT BASIN DETAILS:

Sediment basins were not placed along the corridor as it is highly developed Residential Arterial. To place a sediment basin would create a disturbance disproportional to the overall site and disturbance.

Sediment basins would generate additional RW/Easement impacts.

Note that all outfalls outfall into pipes + closed drainage systems

USE OF ALTERNATIVE AND/OR ADDITIONAL BMPS:

No alternative or additional BMPS will be used on this project.

DISCHARGES INTO OR WITHIN ONE LINEAR MILE UPSTREAM OF AND WITHIN THE SAME WATERSHED AS, ANY PORTION OF A BIOTA IMPAIRED STREAM SEGMENT

All outfalls are either located further than 1 linear mile upstream or outside of the watershed of an impaired stream segment that has been listed for criteria violated, "Bio F" (Impaired fish community) and/or "Bio M" (Impaired macro Invertebrate community), within Category 4a, 4b or 5, and the potential cause is either "NP" (nonpoint source) or "UR" (urban runoff).

STREAM AND OPEN-WATER BUFFER ENCROACHMENTS

Stream Buffers, as defined by O.C.G.A. 12-7-1, are not impacted by this project.

Non-exempt activities shall not be conducted within the 25- or 50-foot undisturbed stream buffers as measured from the point wrested vegetation without first acquiring the necessary variances and permits.

The Contractor is not authorized to enter into stream buffers, except as described in the table below:

Name or Number of Stream or Other Water Body Type	Location of Buffered Streams and State Waters**			Stream Type (Warm/Cold Water)*	Buffer Impacted? (Yes/No)	Buffer Variance Required? (Yes/No)
	Stream Alignment	Begin Station and Offset	End Station and Offset			
There Are No Allowable Construction Activities Within The Buffer and/or Stream						

Unless noted otherwise, utility companies will be submitting the required permits/variances in conjunction with the impacts caused by their activities. If utility impacts are covered by the Department's stream buffer variance, this shall be noted in the buffer-variance-required column.

* Warm water streams have a 25-foot minimum buffer as measured from the wrested vegetation. Cold water streams have a 50-foot buffer as measured from the wrested vegetation.
 **Locations are approximate, a detailed location of stream buffers and authorized work areas are shown on the individual BMP sheets

WATER QUALITY INSPECTING AND SAMPLING PROCEDURES

See Special Provision 167 and other contract documents for the inspecting and sampling procedures.

READY MIX CHUTE WASH DOWN

The washing of ready-mix concrete drums and dump truck bodies used in the delivery of Portland cement concrete is prohibited on this site.

In accordance with Standard Specification 107: Legal Regulations and Responsibility to the Public, only the discharge chute utilized in the delivery of Portland cement concrete may be rinsed free of fresh concrete remains. The Contractor shall excavate a pit outside of State water buffers, at least 25 feet from any storm drain and outside of the travelled way, including shoulders, for a wash-down pit. The pit shall be large enough to store all wash-down water without overtopping. Immediately after the wash-down operations are completed and after the wash-down water has soaked into the ground, the pit shall be filled in, and the ground above it shall be graded to match the elevation of the surrounding areas. Alternate wash-down plans must be approved by the Project Engineer.

Wash-down plans describe procedures that prevent wash-down water from entering streams and rivers. Never dispose of wash-down water down a storm drain. Establish a wash-down pit that includes the following: (1) a location away from any storm drain, stream, or river, (2) access to the vehicle being used for wash down, (3) sufficient volume for wash-down water, and (4) permission to use the area for wash down.

On sites where permission or access to excavate a wash-down pit is unavailable, the Contractor may have to wash-down into a sealable 55-gallon drum or other suitable container and then transport the container to a proper disposal site. For additional information, refer to the Georgia Small Business Environmental Assistance Program's "A Guide for Ready Mix Chute/Hopper Wash-down".

SAMPLING GENERAL NOTES:

Representative sampling may be utilized on this project as explained here. The individual outfall drainage basins along the project corridor have been carefully evaluated and compared on the basis of four characteristics: the type of construction activity, the disturbed acreage, the average slope about the outfall, and the soil erosion index 0-10, 10 being the most erodible soil. The construction activity types are new road on fill, new road in cut, road widening, and maintenance/safety. The disturbed area classes are less than or equal to 1 acre, greater than 1 acre to less than 2 acres, and equal to or greater than 2 acres. The average outfall slope is mild if it is equal to or less than 0.03, and steep if it is greater than 0.03. The soil erosion index is low if it is less than or equal to 5 and high if it is greater than 5. After evaluation of these characteristics as presented in the project's drainage area map, hydrology and hydraulic studies, construction plans, geotechnical soil survey, and erosion sedimentation and pollution control plans, the Department has determined that the representative sampling scheme shown below is valid for the duration of the project. The table shows the groups of similar outfall drainage basins.

The increase in turbidity at the specified locations in the table below will be representative of the alternate outfall drainage basins when similar outfall drainage basins exist. Approved primary and alternate representative sampled features are identified in the table below.

Note: The Total Site Area is 3.44 Acres

Primary Sampled Feature	Location (Station and Offset)	Name of Receiving Water	Applicable Construction Stage for Sampling	Sampling Type (Outfall or Receiving Water)	Drainage Area for Receiving Water (mi ²)	Upstream Disturbed Area (acres) (Area flowing over disturbed)	Warm or Cold Water Stream	Appendix B NTU Value (Outfall Sampling Only)	Allowable NTU Increase (Receiving Water Sampling Only)	Location Description	Construction Activity	Representative Sampling Scheme OUTFALL CHARACTERISTICS			
												Disturbed Area (acres)	Average Outfall Slope (Rise/Run)	Soil Erosion Index	Represented Outfall Drainage Basin
PRIMARY	4 71+32 42' LT Old Carriage Dr	Kimberly Creek	Initial, Intermediate	Outfall	3.1	1.06	Warm	75	NA	24" Pipe Outfall	Sidewalk	0.08	1.2%	6.31	Outfall 4
ALTERNATE	3 51+30 115' LT School Entrance	Kimberly Creek	Initial, Intermediate	Outfall	3.1	0.33	Warm	75	NA	24" Pipe Outfall	Sidewalk	0.14	1.1%	6.31	Outfall 3

The primary sampled features specified should be used as the initial sampling locations. An alternate sampled feature may be used if additional sampling is required or to replace a primary sampled feature that is no longer located within the active phase of construction.

	<p>GEORGIA DEPARTMENT OF TRANSPORTATION</p>	<p>NTS</p>	REVISION DATES	STATE OF GEORGIA DEPARTMENT OF TRANSPORTATION
				OFFICE: INNOVATIVE DELIVERY ESPCP GENERAL NOTES
				SRTS - FULTON BETHUNE ELEMENTARY
				DRAWING No. 51-002