LOCATION	NO. OF LOC.	MARK	LENGTH FT.	LENGTH IN.	NO. BARS REQ'D.	TYPE	AG	B FT.	B IN.	C FT.	C IN.	D FT.	D IN.	E FT.	E IN.	F FT.	F IN.	H FT.	H IN.	J FT.	J IN.	K FT.	K IN.	N	θ
SPAN 1	1																								
		300	5	0	2	1																			
		400A	48	4	162	1																			
		401A	30	4	36	1																			
		403A	4	10	2	3		4	1	0	9														
		404	35	11	6	1																			
		405A	9	8	21	31	4 4	0	9	4	1	4	1												
		405B	7	7	6	25	4 4	0	9	2	8														
		406	4	4	8	29		1	0	0	9	1	0												
		407A	8	8	12	1																			
		408A	9	1	21	25	4 4	0	7	3	7														
		408B	5	9	6	25	4 4	0	7	1	11														
		500	36	4	191	2		34	8	0	10	0	10												
		501	34	11	191	1																			
		502	5	9	192	23		0	9	2	6	2	6											96	
		503	4	11	192	23		0	5	2	3	2	3											84	
		504A	6	7	12	46		3	9	1	2	0	3	1	0	1	0								
		504B	7	3	21	46		3	9	1	10	0	3	1	0	1	0								
		505	33	6	1	1																			
		506A	2	11	15	24		1	3	0	10	0	10	0	7	0	7								
		506B	6	1	35	3		4	10	1	3														
		507	28	6	2	1																			
		508A	8	8	6	1																			
		509A	7	6	12	1																			
		600	10	0	54	1																			
		800	33	6	2	1																			
		801	28	6	1	1																			
		802A	8	8	3	1																			
		900A	13	2	18	14		5	10	0	9	2	11	0	9	2	11								
		900B	7	1	12	14		1	11	2	3	2	11	0	0	0	0								
SPAN 2	1																								
		300	5	0	4	1																			
		400A	48	4	162	1																			
		401B	31	4	36	1																			
		403A	4	10	4	3		4	1	0	9														
		405A	9	8	42	31	4 4	0	9	4	1	4	1												
		405B	7	7	12	25	4 4	0	9	2	8														
		406	4	4	24	29		1	0	0	9	1	0												
		407A	8	8	12	1																			
		408A	9	1	21	25	4 4	0	7	3	7														
		408B	5	9	6	25	4 4	0	7	1	11														
		500	36	4	191	2		34	8	0	10	0	10												
		501	34	11	191	1																			
		502	5	9	198	23		0	9	2	6	2	6											96	
		503	4	11	198	23		0	5	2	3	2	3											84	
		507	28	6	4	1																			
		508A	8	8	12	1																			
		509A	7	6	12	1																			
		600	10	0	54	1																			
		800	33	6	4	1																			
		801	28	6	2	1																			
		802A	8	8	6	1																			

LOCATION	NO. OF LOC.	MARK	LENGTH FT.	LENGTH IN.	NO. BARS REQ'D.	TYPE	AG	B FT.	B IN.	C FT.	C IN.	D FT.	D IN.	E FT.	E IN.	F FT.	F IN.	H FT.	H IN.	J FT.	J IN.	K FT.	K IN.	N	θ
SPANS 3 OR 4	2																								
		300	5	0	4	1																			
		400B	47	11	213	1																			
		401C	34	8	48	1																			
		402	5	10	233	3		5	0	0	10														
		403B	6	4	4	3		5	7	0	9														
		405C	12	8	40	31	4 4	0	9	5	7	5	7												
		405D	9	3	16	25	4 4	0	9	3	6														
		406	4	4	24	29		1	0	0	9	1	0												
		407B	6	3	32	1																			
		408C	12	1	20	25	4 4	0	7	5	1														
		408D	8	11	8	25	4 4	0	7	3	6														
		500	36	4	233	2		34	8	0	10	0	10												
		501	34	11	233	1																			
		502	5	9	288	23		0	9	2	6	2	6												96
		503	4	11	288	23		0	5	2	3	2	3												84
		507	28	6	8	1																			
		508B	6	3	32	1																			
		509B	5	1	16	1																			
		800	33	6	4	1																			
		801	28	6	2	1																			
		802B	6	3	8	1																			
SPAN 5	1																								
		300	5	0	2	1																			
		400B	47	11	213	1																			
		401D	33	11	48	1																			
		402	5	10	233	3		5	0	0	10														
		403B	6	4	2	3		5	7	0	9														
		404	35	11	8	1																			
		405C	12	8	20	31	4 4	0	9	5	7	5	7												
		405D	9	3	8	25	4 4	0	9	3	6														
		406	4	4	24	29		1	0	0	9	1	0												
		407B	6	3	32	1																			
		408C	12	1	20	25	4 4	0	7	5	1														
		408D	8	11	8	25	4 4	0	7	3	6														
		500	36	4	233	2		34	8	0	10	0	10												
		501	34	11	233	1																			
		502	5	9	280	23		0	9	2	6	2	6												96
		503	4	11	280	23		0	5	2	3	2	3												84
		504C	8	1	15	46		5	3	1	2	0	3	1	0	1	0								
		504D	8	9	22	46		5	3	1	10	0	3	1	0	1	0								
		505	33	6	1	1																			
		506A	2	11	16	24		1	3	0	10	0	10	0	7	0	7								
		506C	7	7	32	3		6	4	1	3														
		507	28	6	4	1																			
		508B	6	3	16	1																			
		509B	5	1	16	1																			
		600	10	0	52	1																			
		800	33	6	2	1																			
		801	28	6	1	1																			
		802B	6	3	4	1																			
		900C	10	9	32	14		3	5	0	9	2	11	0	9	2	11								
		900B	7	1	16	14		1	11	2	3	2	11	0	0	0	0								

STATE	PROJECT NUMBER	SHEET NO.	TOTAL SHEETS
GA.	BHSLB-0656-00(002)	91	169

BRIDGE NO. 1

J.B. Trimble, Inc.
2550 Heritage Ct. SE. Suite 250
Atlanta GA 30339-3062
(770) 952-1022

GEORGIA
DEPARTMENT OF TRANSPORTATION
PRECONSTRUCTION DIVISION-OFFICE OF BRIDGE DESIGN

SUPERSTRUCTURE REINFORCING SCHEDULE
CR 172 (POBIDDY ROAD) OVER FLINT RIVER

TALBOT/UPSON COUNTIES — BHSLB-0656-00(002)

SCALE: NO SCALE — AUGUST 2006

DRAWING NO. 35-19
BRIDGE SHEET 19 OF 20

REVISIONS — DATE — BY

DESIGNED SHG — CHECKED MCD — REVIEWED RJS
DRAWN SHG — DESIGN GROUP EJC — APPROVED PVL

n:\tra\9930\wo * 8\dgn\bridge\final\34310rsl.dgn 4/2/2012