

GENERAL NOTES

PROJECT SPECIFIC NOTES

STATE	PROJECT NUMBER	SHEET NO.	TOTAL SHEETS
GA.	STP-2928(1)	4	324
REVISION DATES			
10/11/07			



Dig Safely.
1-800-282-7411
770-623-4344

2. THE FOLLOWING UTILITIES HAVE FACILITIES IN THE PROJECT AREA:

- MR. PATRICK BOWIE (ELECTRICAL)
CITY OF LAGRANGE
200 RIDLEY AVENUE
LAGRANGE, GEORGIA 30240
(706) 883-2010
- MR. CHUCK REDMOND (ELECTRICAL)
DIVERSE POWER
P.O. BOX 160
1400 SOUTH DAVIS ROAD
LAGRANGE, GEORGIA 30241
(706) 845-2000
- MR. PATRICK BOWIE (GAS)
CITY OF LAGRANGE
200 RIDLEY AVENUE
LAGRANGE, GEORGIA 30240
(706) 883-2010
- MR. BLAIR H. NORTHERN, JR., P.E. (GAS)
PLANTATION PIPELINE COMPANY
100 ALDERMAN DRIVE, SUITE 200
ALPHARETTA, GEORGIA 30005
(770) 751-4109
- MR. PATRICK BOWIE (SEWER)
CITY OF LAGRANGE
200 RIDLEY AVENUE
LAGRANGE, GEORGIA 30240
(706) 883-2010
- MR. PATRICK BOWIE (WATER)
CITY OF LAGRANGE
200 RIDLEY AVENUE
LAGRANGE, GEORGIA 30240
(706) 883-2010
- MS. SUZANNE S. TAYLOR, MANAGER (TELEPHONE)
BELLSOUTH TELECOMMUNICATIONS, INC.
2424 WILLIAMS ROAD
COLUMBUS, GEORGIA 31909
(706) 571-3661
- MR. CLAYTON JENNINGS (CABLE TV)
CHARTER COMMUNICATIONS
127 MATTOX COURT
LAGRANGE, GEORGIA 30241
(706) 882-1479
- PLANTATION PIPELINE COMPANY (PETROLEUM)

- THERE IS NO SUITABLE PLACE TO BURY ANY CONSTRUCTION DEBRIS WITHIN THE PROJECT LIMITS. THE CONTRACTOR SHOULD FIND A SUITABLE PLACE TO DISPOSE OF CONSTRUCTION DEBRIS AT NO ADDITIONAL COST TO THE DEPARTMENT.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO FURNISH AN ENVIRONMENTALLY APPROVED BORROW SITE AND DISPOSAL SITE FOR THE PROJECT. THE DISTRICT MATERIALS ENGINEER SHOULD BE NOTIFIED NOT LESS THAN SIX WEEKS PRIOR TO THE CLEARING OF A BORROW OR WASTE PIT.
- ALL DRIVEWAYS, WHERE ACCESS IS ALLOWED, SHALL BE PLACED AS DIRECTED BY THE ENGINEER IN ACCORDANCE WITH RULES AND REGULATIONS FOR CONTROL AND PROTECTION OF DEPARTMENT OF TRANSPORTATION RIGHTS-OF-WAY. ALL DRIVEWAYS THAT ARE TO BE RECONSTRUCTED SHALL BE REPAVED WITH ASPHALT, WITH THE EXCEPTION TO CONCRETE DRIVEWAYS WHICH SHALL BE REPLACED WITH CONCRETE. THE DRIVEWAY LOCATIONS INDICATED ON THE PLANS ARE FROM THE BEST AVAILABLE DATA. THE CONTRACTOR SHALL (UNLESS OTHERWISE NOTED ON THE PLANS) CONSTRUCT NEW DRIVEWAYS TO MATCH THE ACTUAL FIELD LOCATION OF EXISTING DRIVEWAYS WHERE THEY ARE NOT IN CONFLICT WITH THE RULES AND REGULATIONS. THE CONTRACTOR SHALL OBTAIN THE APPROVAL OF THE ENGINEER PRIOR TO MAKING ANY REVISIONS SUCH AS TO LOCATION, WIDTH AND/OR NUMBER OF DRIVES TO BE CONSTRUCTED. WHERE REQUIRED, THE DRIVES SHALL BE PAVED AS FOLLOWS:

ASPHALTIC CONCRETE DRIVES
 RESIDENTIAL - RECYCLED ASPH CONC 12.5 MM SUPERPAVE, GROUP 2 ONLY, INCL BITUM MATL & H LIME - 165*/SY
 - 4" GRADED AGGREGATE BASE

 COMMERCIAL - RECYCLED ASPH CONC 12.5 MM SUPERPAVE, GROUP 2 ONLY, INCL BITUM MATL & H LIME - 165*/SY
 - RECYCLED ASPH CONC 19 MM SUPERPAVE, GP 1 OR 2, INCL BITUM MATL & H LIME - 220*/SY
 - 6" GRADED AGGREGATE BASE

CONCRETE DRIVES
 RESIDENTIAL - 4" CONCRETE DRIVEWAY WITH 6" VALLEY GUTTER
 COMMERCIAL - 6" CONCRETE DRIVEWAY WITH 8" VALLEY GUTTER

 REFER TO GEORGIA DOT STD. 9031H FOR RURAL TURNOUT DETAILS.
- ALL DRIVES SHALL BE PAVED TO THE RIGHT-OF-WAY LINE EXCEPT AS NOTED ON PLANS.
- ALL EXISTING PIPES TO BE ABANDONED SHALL BE PLUGGED AND FILLED WITH FLOWABLE FILL MATERIAL. FOR ALL EXISTING PIPES TO BE REMOVED, COSTS FOR REMOVAL SHALL BE INCLUDED IN THE PRICE BID FOR GRADING COMPLETE.
- THIS PROJECT WILL REQUIRE AN NOI.
- ALL EXISTING GUARDRAIL SHALL BE REMOVED. TEMPORARY BARRIER SHALL BE PLACED IN FRONT OF ALL EXISTING GUARDRAIL BEFORE REMOVAL OF THE GUARDRAIL.

Pipe Culvert Material Alternates For Piedmont/Blue Ridge Region

TYPE OF PIPE INSTALLATION	CONCRETE	CORRUGATED STEEL AASHTO M-36		CORRUGATED ALUMINUM AASHTO M-196	PLASTIC		
		ALUMINUM COATED (TYPE 2) CORR. STEEL	PLAIN ZINC COATED	PLAIN UNCOATED ALUMINUM	CORR. POLY-ETHYLENE AASHTO M-252	CORR. POLY-ETHYLENE SMOOTHED LINED AASHTO M-294 TYPE "S"	POLY VINYL CHLORIDE (PVC) PROFIL WALL AASHTO M-304
LONGITUDINAL INTERSTATE AND TRAVEL BEARING	X						
LONGITUDINAL NON-INTERSTATE AND NON-TRAVEL BEARING	X	X		X		X	X
STORM DRAINS	CROSS	ADT < 250	X	X	X	X	X
		GRADE ≤ 10% 250 < ADT < 1500	X	X*	X		
	DRAIN	ADT > 1500	X				
		GRADE > 10%		X	X	X	X
SIDE DRAIN	X	X	X	X		X	X
PERMANENT SLOPE DRAIN		X	X	X		X	X
PERFORATED UNDERDRAIN		X	X	X	X	X	

* This type pipe can be used if the addition of Type "B" Coating (AASHTO M-190, Half Bituminous Coated with Paved Invert) is utilized.

NOTES:

- Allowable materials are indicated by an "X".
- Structural requirements of storm drain pipe will be in accordance with Georgia Standard I030-D or I030-P, whichever is applicable, and the Standard Specifications.



PARSONS
5890 TRIANGLE PARKWAY, SUITE 100
NORCROSS, GA 30092

STATE OF GEORGIA
DEPARTMENT OF TRANSPORTATION

GEORGIA DEPARTMENT OF TRANSPORTATION
GENERAL NOTES
S.R.14-U.S.29 IN LAGRANGE

DRAWING No
4-01

\$DATES
\$DGNS
\$PRFS