

SIGNING & MARKING SUMMARY OF QUANTITIES

TRAFFIC STRIPE		
DESCRIPTION	UNIT	QUANTITY
THERMOPLASTIC SOLID TRAF STRIPE, 5 IN. WHITE	LF	1469
THERMOPLASTIC SOLID TRAF STRIPE, 5 IN. YELLOW	LF	689
THERMOPLASTIC SOLID TRAF STRIPE, 24 IN. WHITE	LF	96
THERMOPLASTIC SOLID TRAF STRIPE, 8 IN. WHITE	LF	1298
THERMOPLASTIC SKIP TRAF STRIPE, 5 IN. WHITE	GLF	1259
PREFORMED SOLID PVMT MKG, 5 IN. WHITE	LF	1391
PREFORMED SKIP PVMT MKG, 5 IN. WHITE	GLF	1418
PREFORMED SOLID PVMT MKG, 5 IN. YELLOW	LF	662
THERMOPLASTIC TRAFFIC STRIPING, WHITE	SY	184
THERMOPLASTIC TRAFFIC STRIPING, YELLOW	SY	27
PREFORMED PLASTIC PVMT MARKING, YELLOW, TP PB	SY	8

SUMMARY OF QUANTITIES-STANDARD SIGNS																									
STATION	INSTL. NO.	SIGN CODE	HIGHWAY SIGNS												SQUARE TUBE POST						BREAKAWAY SIGN SUPPORT (EACH)				
			TP 1 MATL. REFL SHEETING TP 3			TP 2 MATL. REFL SHEETING TP 3			TP 1 MATL. REFL SHEETING TP 9			TP 2 MATL. REFL SHEETING TP 9			TYPE 7		TYPE 8		TYPE 9						
			SIZE	QUANTITY	SQUARE FEET	LENGTH (FEET)	QUANTITY	TOTAL LENGTH	LENGTH (FEET)	QUANTITY	TOTAL LENGTH		LENGTH (FEET)	QUANTITY	TOTAL LENGTH										
Mainline																									
SR 139																									
27+71 LT		R4-7 (24)										24X30	1	5	12.50	1	12.50								
32+90		R4-7 (24)										24X30	1	5	12.50	1	12.50								
RAMP A																									
74+00 RT		R8-3a (24)										24X24	1	4	12.0	1	12.0								
73+80 RT		R5-10b (30)										30X18	1	3.75	11.5	1	11.5								
RAMP C																									
51+50 LT		R5-10b (30)										30X18	1	3.75	11.5	1	11.5								
51+00 LT		R1-2 (30)										30X30X30	1	2.71	12.17	1	12.17								
RAMP D																									
64+90 RT		R5-1 (30)										30X30	1	6.25	12.50	1	12.50								
TOTAL												30.46			84.67										

WORDS (EACH)	TYPE 1
PREFORMED, WHITE	2
THERMOPLASTIC, WHITE	1

RAISED PVMT MARKERS (EACH)		
LOCATION	REFLECTIVE-RAISED	
	TWO WAY YELLOW	ONE WAY CLEAR/RED
	TYPE 1	TYPE 3
ON SOLID YELLOW LINES	12	
ON SOLID WHITE LINES		43
ON SKIP WHITE LINES		34
ON WHITE ISLANDS		26
TOTALS	12	103

ARROWS (EACH)		
DESCRIPTION	QUANTITY	
	TYPE 2	TYPE 3
	THERMOPLASTIC, WHITE	5
PREFORMED, WHITE	5	1

SIGNING GENERAL NOTES

- ALL STANDARD HIGHWAY SIGNS SHALL BE FABRICATED AND ERECTED IN ACCORDANCE WITH THE DETAILS SHOWN IN THE PLANS, THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, CURRENT EDITION, AND THE GEORGIA SPECIFICATIONS, SUPPLEMENTAL SPECIFICATIONS, AND/OR SPECIAL PROVISIONS.
- SIGN ERECTION STATIONS ARE APPROXIMATE AND MAY BE ADJUSTED TO MEET FIELD CONDITIONS WHERE NECESSARY, BUT SHALL BE WITHIN THE LIMITATIONS SET FORTH IN THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, CURRENT EDITION. NO SIGN LOCATION SHALL BE CHANGED BY THE CONTRACTOR OR BY THE PROJECT ENGINEER WITHOUT PRIOR APPROVAL FROM THE OFFICE OF TRAFFIC SAFETY AND DESIGN.
- ALL STANDARD HIGHWAY SIGNS SHALL BE ERECTED AT A HEIGHT OF 7 FEET ABOVE THE NORMAL EDGE OF PAVEMENT TO THE BOTTOM OF THE SIGN OR ASSEMBLY.
- HORIZONTAL CLEARANCE FOR STANDARD HIGHWAY SIGNS ON INTERSTATE HIGHWAYS SHALL BE 32 FEET FROM THE NORMAL EDGE OF PAVEMENT TO THE NEARER EDGE OF THE SIGN(S), UNLESS SPECIFIED OTHERWISE IN THE PLANS. HORIZONTAL CLEARANCE FOR STANDARD HIGHWAY SIGNS ON RAMPS SHALL BE 2 FEET FROM THE NORMAL EDGE OF PAVED SHOULDER, OR EDGE OF GRADED SHOULDER WHEN PRESENT.
- HORIZONTAL CLEARANCE FOR STANDARD HIGHWAY SIGNS ON ALL OTHER ROADWAYS SHALL BE 6 FEET FROM THE EDGE OF THE PAVED SHOULDER OR 12 FEET FROM THE NORMAL EDGE OF PAVEMENT TO THE NEARER EDGE OF THE SIGN(S), WHICHEVER IS GREATER. THE HORIZONTAL CLEARANCE IN NON-MOUNTABLE CURB SECTIONS SHALL BE AT LEAST 2 FEET FROM THE CURB FACE TO THE NEARER EDGE OF THE SIGN(S).
- HORIZONTAL CLEARANCE FOR STANDARD HIGHWAY SIGNS MOUNTED BEHIND GUARD RAIL SHALL BE 6 FEET FROM THE FACE OF THE GUARD RAIL TO THE NEARER EDGE OF THE SIGN(S).
- SINGLE PLATE, HORIZONTAL RECTANGULAR SIGNS OVER 48 INCHES IN WIDTH SHALL BE MOUNTED ON TWO POSTS WITH 2 EACH 2 INCH x 1/4 INCH x (WIDTH OF SIGN) ALUMINUM OR GALVANIZED STEEL STRAPS. THE STRAPS SHALL BE FLUSH WITH THE BACK OF THE SIGN WITH ONE EACH ACROSS THE TOP AND BOTTOM OF THE SIGN. THE CENTERLINE OF EACH POST SHALL BE INSET 1/8TH OF THE SIGN WIDTH FROM THE EDGE OF THE SIGN. SIGN PLATE BOLT HOLES SHALL BE 1/2 INCH DIAMETER, DRILLED OR PUNCHED, AS SHOWN ON THE SIGN PLATE DETAILS.
- EACH 42 OR 48 INCH WIDE x 18 OR 24 INCH HIGH SIGN REQUIRES ONE 2 INCH x 1/2 INCH x (WIDTH OF SIGN) ALUMINUM OR GALVANIZED STEEL STRAP LOCATED IN THE CENTER OF THE SIGN AND FLUSH WITH THE BACK OF THE SIGN.
- SIGN ASSEMBLIES SHALL BE MOUNTED ON ALUMINUM OR GALVANIZED STEEL STRAP FRAMES. FOR DETAILS AND STRAP SPECIFICATIONS REFER TO SIGN ASSEMBLY-TYPICAL FRAMING DETAILS.
- TYPE 111 (ENCAPSULATED LENS) REFLECTIVE SHEETING SHALL BE USED FOR ALL STANDARD HIGHWAY SIGNS REQUIRING REFLECTORIZED BACKGROUNDS EXCEPT AS SPECIFIED BELOW OR SPECIFIED OTHERWISE IN THE PLANS. EITHER CLASS 1 OR CLASS 2 ADHESIVE BACKING IS PERMISSIBLE.
- TYPE 1X (WIDE ANGLE PRISMATIC) REFLECTIVE SHEETING SHALL BE USED FOR ALL RED SERIES SIGNS (R1-1, R1-2, R1-3A, R1-4A, R5-1, R5-1A).
- TYPE 1X (WIDE ANGLE PRISMATIC) FLUORESCENT YELLOW GREEN REFLECTIVE SHEETING SHALL BE USED FOR SCHOOL ZONE (S1-1, S2-1, S3-1, S4-3, AND THE TOP PORTION OF THE S5-1) SIGNS, BICYCLE CROSSING (W11-1) SIGNS, AND PEDESTRIAN CROSSING (W11-2 AND W11A-2) SIGNS. SIGNS WITHIN THE SAME ASSEMBLY AS THE SCHOOL ZONE SIGNS SPECIFICALLY LISTED ABOVE AND ALL REGULATORY SIGNS PLACED AS PART OF THE SCHOOL ZONE SIGNING SHALL HAVE TYPE 1X (WIDE ANGLE PRISMATIC) REFLECTIVE SHEETING BACKGROUNDS OF THE APPROPRIATE COLOR.
- TYPE 1X (WIDE ANGLE PRISMATIC) FLUORESCENT YELLOW REFLECTIVE SHEETING SHALL BE USED FOR ALL WARNING SIGNS.
- A 1/4 INCH MINIMUM AIR SPACE SHALL BE REQUIRED BETWEEN ALL SIGN PLATES WITHIN AN ASSEMBLY.
- WHERE SIGNS WITHIN AN ASSEMBLY EXTEND BELOW THE STANDARD MOUNTING HOLES ON THE POST(S), ADDITIONAL 3/8 INCH DIAMETER HOLES, DRILLED OR PUNCHED, SHALL BE REQUIRED TO PROPERLY MOUNT THE ASSEMBLY.
- INTERSTATE SHIELDS SHALL CONTAIN THE WORD GEORGIA. ALL INTERSTATE, U.S., AND GEORGIA SHIELDS REQUIRING ALT., BUS, COMM. LOOP, OR SPUR SHALL USE 4 INCH SERIES "D" LETTERS. REFER TO THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, CURRENT EDITION, FOR DETAILS.
- FOR DETAILS OF SPECIAL DESIGN HIGHWAY SIGNS, SEE DETAILS OF MISCELLANEOUS SIGNS.
- REFER TO PLAN SHEETS FOR LOCATION OF THE DISTRICT ENGINEERS' OFFICE TO BE SHOWN ON ALL R552-1 (LIMITED ACCESS) SIGNS IN THIS PROJECT, IF ANY.
- CONTRACTOR WILL, AS REQUESTED BY THE DISTRICT TRAFFIC OPERATIONS ENGINEER, BE REQUIRED TO REMOVE ANY EXISTING SIGNS THAT ARE DUPLICATED OR ARE CONTRARY TO THESE SIGN PLANS.

REVISION DATES		STATE OF GEORGIA DEPARTMENT OF TRANSPORTATION OPERATIONS DIVISION-OFFICE OF MAINTENANCE	
		SUMMARY OF QUANTITIES	
		DISTRICT 7 BRIDGE JACKING SR-139 (RIVERDALE RD) OVER I-285	
		DRAWING No. 06-02	

