

SUMMARY OF DRIVEWAY QUANTITIES					
	RECYCLED ASPH CONC 9.5 mm SUPERPAVE, GP 2 ONLY, INCL BITUM MAT'L & H LIME DESIGN MIX LEVEL "B" 135 LB / 50 YD	RECYCLED ASPH CONC 19.0 mm SUPERPAVE, GP 1 OR 2 ONLY, INCL BITUM MAT'L & H LIME DESIGN MIX LEVEL "B" 220 LB / 50 YD	GR AGGR BASE CRS, 6 INCH, INCL MATL	BITUM TACK COAT	DRIVEWAY CONCRETE, 6 IN TK
AS DIRECTED BY ENGINEER	TN 20	TN 27	SY 240	GL 10	SY 400
TOTALS	20	27	240	10	400

CONCRETE VALLEY GUTTER 8 IN. GA. STD.	
SY	700

* TO BE USED AS DIRECTED BY THE ENGINEER.

RECYCLED ASPHALT CONC. LEVELING, INCL BITUM MAT'L & H LIME	
TN	56

* TO BE USED AS DIRECTED BY THE ENGINEER.

AGGREGATE SURFACE COURSE	
TN	50

CONC SIDEWALK, 4 IN	
SY	106

WATER QUALITY INSPECTIONS	
MO	9

TRAFFIC DETECTION LOOP SYSTEM	
6' x 6' PULSE LOOPS	2 EA
6' x 40' QUADRUPLE PULSE LOOPS	2 EA

WATER QUALITY MONITORING AND SAMPLING	
EA	2

PLASTIC TRAFFIC CONTROL DRUMS (FOR INFORMATION ONLY)	
EA	120

FOR INFORMATION ONLY (TO BE INCLUDED
IN TRAFFIC CONTROL - LUMP SUM)

FOUND BKFILL MATL, TP II	
CY	380

PAVEMENT MARKINGS		
THERMOPLASTIC TRAFFIC STRIPING		
24" SOLID WHITE	LF	79

D:\TMA\000\95501-REV.151...
 G:\1587060\1587060\1587060\CAD\CAD\1587060\02\02.dwg
 P11 Feb 3 09:10:21 2008



DATE	REVISIONS	DATE	REVISIONS