



**TYPE A WOOD POST (FOR "W" BEAM GUARDRAIL)**

NOTE: WOOD POST ARE ALLOWABLE ONLY WHERE SPECIFIED.




SEE SEPARATE STANDARD OR DETAIL FOR POSTS IN TUBE SLEEVE.




WOOD POSTS AND WOOD OFFSET BLOCKS MAY BE ROUGH OR SURFACED. DIMENSIONS FOR WOOD POSTS AND WOOD OFFSET BLOCKS ARE NOMINAL IN ACCORDANCE WITH ACCEPTED LUMBER INDUSTRY STANDARDS.

NOTE: WHERE WOOD OFFSET BLOCK ON STEEL POST IS PERMITTED IN "W" BEAM INSTALLATION, A NAIL OR SCREW FROM POST TO WOOD IS REQUIRED TO PREVENT ROTATION OF THE BLOCK.




NOTE: WHERE WOOD OFFSET BLOCK ON STEEL POST IS PERMITTED IN "W" BEAM INSTALLATION, A NAIL OR SCREW FROM POST TO WOOD IS REQUIRED TO PREVENT ROTATION OF THE BLOCK.



(PLAN VIEW IS SAME AS SHOWN FOR WOOD POST ABOVE)


**TYPE D STEEL POST (FOR "W" BEAM GUARDRAIL)**



SCALE

**MODIFIED STEEL OFFSET BLOCK FOR "T" BEAM GUARDRAIL**

NOTE: MODIFIED STEEL OFFSET BLOCKS ARE USED ONLY WHERE SPECIFIED SEE NOTE 5(c)




FRONT

SIDE

BACK

NO SCALE

**BACK-UP PLATE (FOR "T" BEAM GUARDRAIL)**




FRONT

SAME AS SECTION THROUGH RAIL (STANDARD 4270)

**STANDARD PLASTIC OFFSET BLOCKS**

NOTE: PLASTIC OFFSET BLOCKS SHALL BE OF TYPE LISTED IN GA. DOT OPL OF APPROVED PRODUCTS OR PER STANDARD SPECIFICATIONS.



PLAN


BACK VIEW (FOR "W" BEAM)

BACK VIEW (FOR "T" BEAM)


NOTE: DIMENSIONS ARE SUBJECT TO MANUFACTURER'S TOLERANCES.

NO SCALE


**TYPE D-T STEEL POST (FOR "T" BEAM GUARDRAIL)**



SCALE



FRONT




PLAN

**COMPOSITE OFFSET BLOCKS (FOR "W" BEAM)**

NOTE: 1. COMPOSITE OFFSET BLOCKS SHALL BE OF TYPE LISTED IN GA. D.O.T. OPL OF APPROVED PRODUCTS OR PER STANDARD SPECIFICATIONS.  
2. UNIFORM WALL THICKNESS OF 0.375".  
3. UNSPECIFIED CORNERS TO BE 0.050" MIN.  
4. UNSPECIFIED TOLERANCES TO BE 0.050".

NOTE: ADDITIONAL DEPTH OFFSETS BELOW ARE SHOWN FOR "W" BEAM. SIMILAR OFFSETS MAY BE APPLIED FOR "T" BEAM GUARDRAIL.  
NOTE: ADDITIONAL DEPTH OFFSETS ARE PERMITTED ONLY WHERE AN ISOLATED POST MUST BE PLACED AT A GREATER THAN NORMAL OFFSET.



PLAN

SIDE VIEW


STEEL POST TO BE PLUMBED AND FOUNDATION CONCRETE POURED AROUND POST TO FINISHED ELEVATION.

PAYMENT FOR GUARDRAIL TO INCLUDE ALL EXTRA WORK AND MATERIALS INCLUDING CONCRETE (CL. A OR CL. B) AND NO. 4 BARS.


IF OFFSET FROM RAIL FACE TO HEADWALL IS LESS THAN 4'-3", POST SPACINGS ARE REDUCED TO 3'-1/2" C.C. ACROSS THE CULVERT WITH 7 SUCH SPACINGS IN ADVANCE AT NO ADDITIONAL PAYMENT.

**GENERAL NOTES:**

- SPECIFICATIONS GEORGIA STANDARD, CURRENT EDITION AND SUPPLEMENTS THERETO.
- STEEL POSTS MAY BE EITHER ROLLED OR WELDED STRUCTURAL SHAPES. STEEL OFFSET BLOCKS SHALL BE ROLLED. WELDED POSTS SHALL BE SEAL WELDED BETWEEN WEB AND FLANGE BEFORE GALVANIZING.
- WHERE WOOD POST OR WOOD OFFSET BLOCKS ARE PERMITTED, THE WOOD SHALL BE TREATED IN ACCORDANCE WITH GEORGIA STANDARD SPECIFICATIONS.
- ALL BOLTS USED FOR FASTENING THE RAIL AND OFFSET BLOCKS TO WOOD POSTS SHALL HAVE SUFFICIENT LENGTH TO EXTEND AT LEAST 1/4" BEYOND THE FULL NUT, UP TO 3" BEYOND.
- (a) "W" BEAM GUARDRAIL: ALL OFFSET BLOCKS SHALL BE 8" DEPTH PLASTIC BLOCKS EXCEPT FOR (d) BELOW.  
(b) "T" BEAM GUARDRAIL: STANDARD INSTALLATION WILL USE 8" DEPTH PLASTIC BLOCKS UNLESS OTHERWISE APPROVED.  
(c) 13 3/4" DEPTH MODIFIED STEEL OFFSETS MAY BE SPECIFIED WHERE JUSTIFIED FOR MORE SEVERE CONDITIONS. PAY ITEM IS --GUARDRAIL, TP T, MODIFIED OFFSET BLOCK---PER LIN. FT.  
(d) WOOD OFFSET BLOCKS MAY BE USED ONLY AT AN ISOLATED LOCATION WITHIN A RUN OF GUARDRAIL, WHERE OTHER BLOCK TYPES WOULD NOT PROVIDE PROPER FIT, AS DETERMINED BY THE ENGINEER OR SHOWN IN THE PLANS.
- POSTS WILL BE SPACED AT 6'-3" C. TO C., UNLESS OTHERWISE NOTED.
- ADDITIONAL LENGTH POSTS, WHERE SPECIFIED, SHALL BE 7'-0" AND 7'-6" LONG FOR "W" BEAM AND "T" BEAM GUARDRAILS RESPECTIVELY, WITH HOLES DIMENSIONED FROM THE POST-TOP THE SAME AS SHOWN.



SIDE



NOTE: WOOD BLOCK(S) WITH OVER 8" DEPTH ALSO PERMITTED.  
LIGHTWEIGHT NAIL OR STAPLES TO RETARD ROTATION.  
SINGLE BOLT CONNECTION.  
TWO (MAXIMUM) WOOD BLOCKS AS NEEDED TO GIVE ADDITIONAL OFFSET.

**ADDITIONAL DEPTH OFFSET BLOCKOUTS (FOR USE WHERE GREATER THAN STANDARD OFFSET IS SPECIFIED)**

DEPARTMENT OF TRANSPORTATION STATE OF GEORGIA			
<b>STANDARD POSTS AND OFFSET BLOCKS FOR "W" &amp; "T" BEAM GUARDRAIL (REPLACES STANDARDS 4011 &amp; 4271)</b>			
SCALE: AS SHOWN REVISED & REDRAWN DEC., 1999			
ADDED COMPOSITE BLOCK	12-18-01	DATE	NUMBER <b>4011A</b>
REV. OFFSET BLK., RAIL HT.	12-27-00	DATE	
BY			
(SUBMITTED)	James A. Kanel STATE ROAD & AIRPORT DESIGN ENGINEER		
(APPROVED)	Paul L. Conley CHIEF ENGINEER		

4/18/02 2:31:11 PM \\GDOT-DSN1\G0PLOT\OCF\Road Design\Tiff-18x12 to Tiff-36x24.acf\wqvuev\c:\documents and settings\wqvuev\Desktop\M002418\Construction\Plan\_Sheet\M002418\_020\_11f\_60-RD-Plans-Review

4/18/02 2:31:11 PM \\GDOT-DSN1\G0PLOT\OCF\Road Design\Tiff-18x12 to Tiff-36x24.acf\wqvuev\c:\documents and settings\wqvuev\Desktop\M002418\Construction\Plan\_Sheet\M002418\_020\_11f\_60-RD-Plans-Review