STATE	PROJECT NUMBER	SHEET NO.	TOTAL SHEETS
GA.	CSNHS-M002-00(701)	65	71

TYPE 1 SPILLWAY (TYPICAL USE: ON GRADES, FILLS OVER 5 FT.)



	NORMAL	⊗ REDUCED
W	13'-0"	9'-9" MIN
x : y	4 : 1	3 : 1 TYP.
S	16'-0"	12'-0" MIN

⊗ PERMITTED ONLY WHERE BRIDGE ELEMENTS OBSTRUCT. NORMALS DIMENSIONS.



SECTION A-A



SECTION B-B



SECTION C-C



SECTION D-D



SECTION E-E



SECTION F-F.

TYPE 3 SPILLWAY

(TYPICAL USE: ON GRADES, FILLS 5. FT. OR LESS)



	NORMAL	⊗ REDUCED
W	13'-0"	9'-9" MIN.
X : Y	4 : 1	3 : 1 TYP.
S	16'-0"	12'-6" MIN.

⊗ PERMITTED ONLY WHERE BRIDGE ELEMENTS OBSTRUCT NORMAL DIMENSIONS.

SEC G-G



SEC. H-H



OUTLET APRON



NOTE:
APRON IS REQUIRED AT ALL SLOPE DRAIN PIPE OUTLETS UNLESS CONCRETE DITCH PAVING OR RIP RAP PROTECTION IS PROVIDED.

APRON QUANTITY: 0.17 CU. YDS OF CL "A" OR CL "B" CONC.



NOTE: APRON CONSTRUCTED FROM SAND CEMENT BAG RIP RAP, MORTAR RUBBLE MASONRY OR STONE GROUT RIP RAP MAY BE SUBSTITUTED FOR CONCRETE APRON.

SLOPE DRAIN PIPE DIAMETERS	
PIPES I.D. (INCHES)	AREA DRAINING INTO SPILLWAY - (SQ. FT.)
15"	TO 24,100
18"	OVER 24,100

SLOPE DRAIN PIPE ELBOW ANGLES		
EMBANKMENT SLOPE	ELBOW IN SPILLWAY	ELBOW AT OUTLET
STEEPER THAN 4:1	Ø = 60° ±	α = 30° ±
4:1 OR FLATTER	Ø = 75° ±	α = 15° ±

TYPE 4 SPILLWAY (TYPICAL USE: IN SAGS OR LOW AREAS, FILLS 5 FT. OR LESS),



	NORMAL	⊗ REDUCED
W	13'-0"	9'-9" MIN
x : y	3 : 2	1 : 1 TYP.
S	6'-0"	4'-0" MIN

⊗ PERMITTED ONLY WHERE BRIDGE ELEMENTS OBSTRUCT NORMAL DIMENSIONS.

DETAILS BELOW THIS LINE ARE THE SAME AS SHOWN FOR TYPE 3.

TYPE 2 SPILLWAY

(TYPICAL USE: IN SAGS OR LOW AREAS, FILLS OVER 5 FT.)



	NORMAL	⊗ REDUCED
W	13'-0"	9'-9" MIN
X : Y	3 : 2	1 : 1 TYP.
S	6'-0"	4'-0" MIN

⊗ PERMITTED ONLY WHERE BRIDGE ELEMENTS OBSTRUCT NORMAL DIMENSIONS.

GENERAL NOTES:

1. SPECIFICATIONS: GA. STANDARD, CURRENT EDITION, & SUPPLEMENTS THERETO.
2. PAYMENT FOR SPILLWAY (ANY TYPE) INCLUDES ALL TIE BARS & CONNECTIONS TO APPROACH SLAB.

NOTE: PAYMENT FOR SPILLWAY INCLUDES INDICATED BLOCKOUTS EXCEPT WHERE IT HAS BEEN VERIFIED THAT GUARDRAIL IS NOT REQUIRED.
*IF GUARDRAIL IS WARRANTED AT THE TRAILING END OF 4 OR MORE LANES, BLOCKOUTS FLAGGED WITH AN ASTERISK ARE OMITTED.

BLOCKOUT LOCATIONS FOR GUARDRAIL POST



⊕ VARIED TO MISS BRIDGE PAV. REST

GENERAL REVISION	2-28-90	
BLOCKOUT SPA.	4-27-89	

DEPARTMENT OF TRANSPORTATION
STATE OF GEORGIA

STANDARD CONCRETE SPILLWAYS
(ADJACENT TO APPROACH SLABS)

NO SCALE — REV. & REDR. JUNE, 1985

R.H.G.	DES. R.M.U.	(SUBMITTED) Floyd E. Hartley — STATE ROAD & AIRPORT DESIGN ENGR.
K.L.J.	DRW R.M.U.	
	TRA. G.M.E.	(APPROVED) Hal Kimsey — STATE HIGHWAY ENGINEER
	CHK. R.K.C.	

NUMBER 9017J

FORM EF00003