

SUMMARY OF QUANTITIES

[illegible]

MILEPOSTS

GA. STD. 9033

MILEPOSTS GA. STD. 9033									
STATION		MILEPOST NO.		SIGNS (SQ. FT.)			POSTS (LIN. FT.)		
BEGIN	END	BEGIN	END	TYPE 1(0.08 IN.)			TYPE 2(2.0 LB/LIN. FT.)		
				SIZE	QUANTITY	SQ. FEET	LENGTH	QUANTITY	LIN. FEET
579+25	84+80	3	5	12" x 24"	6	12.00	12	6	72
TOTALS						12.00			72

NOTE:

The ending station and milepost number were computed from data and are approximate, only. It shall be the responsibility of the Engineer to furnish the Office of Traffic Operations with the accurate (not adjusted) field location for the last milepost on this project.

GENERAL NOTES:

1. Delineators shall be placed along the right side of the through Interstate roadways, two(2) feet beyond the outside edge of roadway shoulder or the face of an unmountable curb, or in the line of the guard rail. At Interchanges, delineators shall be located along the outside of ramp curves, i.e., on the left side for ramps curving to the right and on the right side for ramps curving to the left. Spacing on Interstate mainlines shall be 528 feet. Spacing on ramps shall be 100 feet unless otherwise shown on the plans.
2. Installation of delineators shall be with until grassing has been accepted by the State.
3. Red delineators, Type 1 or Type 1A, shall be installed on exit ramps facing toward the ramp terminal beginning at the "Wrong Way" signs and ending at the ramp terminal. Spacing shall be 100 feet unless otherwise shown on the plans.
4. Delineator color shall be the same as the edgeline. For additional information, see Ga. Standard 9030c.