


SINGLE ROW TYPE A SILT FENCE



FENCE TYPE	POST LENGTH	Н	D	w*	TYPICAL USES
TYPE "A"	4 FT.	2'-4"	1'-6"	3′-0"	
TYPE "C"	4 FT.	2′-4"	l'-6"	3'-0"	AT BRIDGE END ROLLS, DOUBLE ROW ALONG STREAMS, WETLANDS AND ENVIRONMENTALLY SENSITIVE AREAS FOR USE OF THIS MATERIAL IN FABRIC CHECKDAMS SEE D-24D.

## NOTES:

- I. WIRE STAPLES SHALL BE AT LEAST 17 GAUGE, WITH LEGS AT LEAST  $\frac{1}{2}$  INCHES LONG AND A CROWN AT LEAST  $\frac{3}{4}$  INCHES WIDE. NAILS SHALL BE AT LEAST 14 GAUGE, I INCH LONG , WITH BUTTON HEADS AT LEAST  $\frac{3}{4}$  INCHES WIDE.
- 2. SEE SECTION 171 FOR PLACEMENT OF NAILS OR STAPLES FOR TYPE A AND TYPE C FENCES.
- 3. THE VERTICAL WIRES FOR THE WOVEN WIRE SUPPORT FENCE SHALL HAVE A MAXIMUM SPACING OF 12 INCHES. THE TOP AND BOTTOM WIRES SHALL BE AT LEAST 10 GAUGE AND ALL OTHER WIRES SHALL BE AT LEAST  $12\frac{1}{2}$  GAUGE.
- 4. TEMPORARY SILT FENCE INSTALLATION IS DIFFERENT THAN THE SILT RETENTION BARRIER INSTALLATION.
- 5. SEE SECTION 171 FOR SILT FENCE SPECIFICATIONS.
- 6. SEE SECTION 894 FOR FENCING SPECIFICATIONS.
- 7. SEE QPL-36 FOR A LIST OF APPROVED SILT FENCE FABRIC.
- 8. TEMPORARY SILT FENCE SHALL NOT BE PLACED WITHIN STATE WATERS UNLESS PERMITTED.

9-2022	DATE	DEPARTMENT OF TRANSPORTATION STATE OF GEORGIA
ADDED HICH TENSILE POLYPROPYLENE O' INTEGRATED FABRIC	REVISION	CONSTRUCTION DETAIL  TEMPORARY SILT FENCE
AL	ВУ	JANUARY 2011 NUMBER D-24A